

**EVINRUDE® E-TEC® G2®**

**200 HP**



<b>Engine Model</b>	(a) C200FL (b) C200FX (c) C200XC (d) C200XO (e) C200PL (f) C200PX (g) C200PXC (h) C200AX (i) C200AXC
<b>Engine Type</b>	V6 66° E-TEC D.I.
<b>Bore x Stroke - in (mm)</b>	3.386 x 3.100 (86 x 79)
<b>Displacement - cu in (cc) L</b>	167 (2744) 2.7L
<b>Gear Ratio</b>	2.17:1
<b>Full Throttle RPM Range</b>	5400-6000 RPM
<b>Weight - lbs (kg)</b>	(a) 530 (240) (b) 541 (245) (c)(h) 533 (242) (d) 528 (239) (e) 496 (225) (f) 507 (230) (g) 512 (233) (h)(i) 541 (246)
<b>Starting</b>	Electric
<b>Controls</b>	iControl Digital Shift & Throttle
<b>Fuel Induction</b>	E-TEC Direct Injection with stratified low RPM combustion mode
<b>Alternator Output*</b>	133 Amps Total / 50 net Dedicated / 14 amps @ idle
<b>Steering</b>	(a)(b) iSteer Dynamic Power Steering (c)(d) Integrated Hydraulic Steering (e)(f)(g) Remote / (h)(i) iDock
<b>Trim Method</b>	Power Trim & Tilt
<b>Trim Range</b>	-6° to 15°
<b>Tilt Range</b>	(a)(b)(c)(d) 81° / (e)(f)(g)(h)(i) 75°
<b>Shaft Length - in (mm)</b>	(a)(e) 20 (508) / (b)(c)(d)(f)(g)(h)(i) 25 (635)
<b>Lubrication</b>	Multi-Point Targeted Oiling
<b>Oil Tank Capacity - gal (L)</b>	On-Engine 3 (11.4) / Accessory 1.8 (6.8), 3 (11.3) & 10 (37.85)
<b>Recommended Oil</b>	Evinrude/ Johnson XD-100 Oil
<b>Recommended Fuel</b>	87 Octane
<b>Counter Rotation</b>	C200XC / C200PXC / C200AXC
<b>Warranty</b>	5-Year Engine** / 5-Year Corrosion
<b>Emissions Compliance</b>	EPA 2013 / CARB 3 STAR / European Union
<b>Mounting Centers - in (mm)</b>	Minimum 26 (660)
<b>Color</b>	Slate Gray with over 400 Color Panel Options
<b>Steering Angle</b>	(a)(b)(c)(d) +/- 32° / (e)(f)(g)(h)(i) +/- 30°
<b>Integrated Features</b>	Dual Axis Rigging / iTrim

\* Variable Voltage Computer Controlled 133 Amp. Current amp calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.  
\*\* 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.