MY25 OUTLANDER 500 (RENTAL)



PACKAGE HIGHLIGHTS

- \cdot 25 in. Tires in 12 in. Steel wheels
- · Full skid plate
- · Glovebox
- · Front dropdown storage

Legion Red

Type 40 hp / 37 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc, single cylinder, liquid cooled Fuel Delivery System Electronic Fuel Injection (EFI) Transmission pDrive primary CVT L / H / N / R / P Drive Train 2WD System Driving assistance N/A Power Steering N/A SUSPENSIONS Front Suspension Double A-arm 9.75 in. (24.8 cm) travel Front Shocks Twin tube Rear Suspension Double A-arm 10.25 in. (26 cm) travel Rear Shocks Twin tube TIRES / WHEELS Front & Rear Tires 25 x 8/10 x 12 in. Wheels 12 in. Steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic twin-piston caliper	ENGINES	500
Transmission pDrive primary CVT L / H / N / R / P Drive Train 2WD System Driving assistance N/A Power Steering N/A SUSPENSIONS Front Suspension Double A-arm 9.75 in. (24.8 cm) travel Front Shocks Twin tube Rear Suspension Double A-arm 10.25 in. (26 cm) travel Rear Shocks Twin tube TIRES / WHEELS Front & Rear Tires 25 x 8/10 x 12 in. Wheels 12 in. Steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic	Туре	
L / H / N / R / P	Fuel Delivery System	Electronic Fuel Injection (EFI)
Driving assistance N/A Power Steering N/A SUSPENSIONS N/A Front Suspension Double A-arm 9.75 in. (24.8 cm) travel Front Shocks Twin tube Rear Suspension Double A-arm 10.25 in. (26 cm) travel Rear Shocks Twin tube TIRES / WHEELS Front & Rear Tires Front & Rear Tires 25 x 8/10 x 12 in. Wheels 12 in. Steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic	Transmission	
Power Steering	Drive Train	2WD System
SUSPENSIONS Front Suspension Double A-arm 9.75 in. (24.8 cm) travel Front Shocks Twin tube Rear Suspension Double A-arm 10.25 in. (26 cm) travel Rear Shocks Twin tube TIRES / WHEELS Front & Rear Tires 25 x 8/10 x 12 in. Wheels 12 in. Steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic	Driving assistance	N/A
Front Suspension Double A-arm 9.75 in. (24.8 cm) travel Front Shocks Twin tube Rear Suspension Double A-arm 10.25 in. (26 cm) travel Rear Shocks Twin tube TIRES / WHEELS Front & Rear Tires 25 x 8/10 x 12 in. Wheels 12 in. Steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic	Power Steering	N/A
9.75 in. (24.8 cm) travel Front Shocks Twin tube Rear Suspension Double A-arm 10.25 in. (26 cm) travel Rear Shocks Twin tube TIRES / WHEELS Front & Rear Tires 25 x 8/10 x 12 in. Wheels 12 in. Steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic	SUSPENSIONS	
Rear Suspension Double A-arm 10.25 in. (26 cm) travel Rear Shocks Twin tube TIRES / WHEELS Front & Rear Tires 25 x 8/10 x 12 in. Wheels 12 in. Steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic	Front Suspension	
10.25 in. (26 cm) travel Rear Shocks Twin tube	Front Shocks	Twin tube
### TIRES / WHEELS Front & Rear Tires	Rear Suspension	
Front & Rear Tires 25 x 8/10 x 12 in. Wheels 12 in. Steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic	Rear Shocks	Twin tube
Wheels 12 in. Steel BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic	TIRES / WHEELS	
BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic	Front & Rear Tires	25 x 8/10 x 12 in.
Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Single 214 mm disc brake with hydraulic	Wheels	12 in. Steel
twin-piston calipers Rear Single 214 mm disc brake with hydraulic	BRAKES	
	Front	
	Rear	

Estimated Dry Weight *	718 lb (325.7 kg)
x W x H (includes mirrors)	86.7 x 47.6 x 48 in. (220.2 x 120.9 x 122 cm)
Vheelbase	53 in. (134.5 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	38 in. (96.7 cm)
Rack Capacity	Front: 120 lb (54.4 kg) / Rear: 240 lb (109 kg)
Storage Capacity	9 gal (34 L)
Towing Capacity	1,830 lb (830 kg)
Fuel Capacity	5.1 gal (19.5 L)
Gauge	4.5 in. Digital Display
Gauge	4.5 in. Digital Display
nstrumentation	N/A
ngnition	Mechanical key
ngnition Lighting	Mechanical key LED headlights and tail lights
ighting	LED headlights and tail lights
Lighting Vinch	LED headlights and tail lights N/A





