MY25 OUTLANDER 6X6 XU+ 1000 T



Boreal Green

PACKAGE HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS)
- · Intelligent Engine Braking (iEB) and driving modes
- · Speed Limiter
- \cdot Selectable 4WD / 6WD with Viso-4Lok auto-locking front differential
- \cdot Continuously Variable Transmission (CVT) with extra low L-gear
- \cdot 26 in. ITP Terracross tires with 14 in. aluminum wheels
- · LED headlights
- \cdot Heavy-duty front bumper
- Heated grips and throttle
- \cdot Rear bed with cargo extenders
- · RF Digitally Encoded Security System (D.E.S.S.)
- Tow ball
- · Painted plastics
- \cdot Horn, flashers and mirrors

Fuel Delivery System Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) Fuel Injection (EFI) Transmission CVT Extra low L / H / N / R / P Drive Train Selectable 4WD / 6WD / Lock 4WD with Visco-4Lok front differential Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter Power Steering Tri-Mode Dynamic Power Steering (DPS) SUSPENSIONS Front Suspension Front Suspension Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel Front Shocks Twin tube Rear Suspension Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel Rear Shocks Twin tube TIRES / WHEELS ITP† Terracross 26 x 8/10 x 14 in. BRAKES I4 in. cast-aluminum	ENGINES	1000
Fuel Injection (EFI) Transmission CVT Extra low L / H / N / R / P Drive Train Selectable 4WD / 6WD / Lock 4WD with Visco-4Lok front differential Driving assistance Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter Power Steering Tri-Mode Dynamic Power Steering (DPS) SUSPENSIONS Front Suspension Front Suspension Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel Front Shocks Twin tube Rear Suspension Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel Rear Shocks Twin tube TIRES / WHEELS ITP† Terracross 26 x 8/10 x 14 in. Front & Rear Tires ITP† Terracross 26 x 8/10 x 14 in. BRAKES Front Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Туре	80 hp, Rotax 976 cc V-twin, liquid cooled
Extra low L / H / N / R / P Extra low L / H / N / R / P Drive Train Selectable 4WD / 6WD / Lock 4WD with Visco-4Lok front differential Driving assistance Work / Standard / Sport modes Intelligent Engine Braking (IEB TM) Speed limiter Power Steering Tri-Mode Dynamic Power Steering (DPS) SUSPENSIONS Front Suspension Front Suspension Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel Front Shocks Twin tube Rear Suspension Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel Rear Shocks Twin tube TIRES / WHEELS Front & Rear Tires Front & Rear Tires ITP† Terracross 26 x 8/10 x 14 in. Wheels 14 in. cast-aluminum BRAKES Front Rear Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Fuel Delivery System	
front differential Driving assistance Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter Power Steering Tri-Mode Dynamic Power Steering (DPS) SUSPENSIONS Front Suspension Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel Front Shocks Twin tube Rear Suspension Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel Rear Shocks Twin tube TIRES / WHEELS ITP† Terracross 26 x 8/10 x 14 in. Wheels 14 in. cast-aluminum BRAKES Front Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Transmission	
Intelligent Engine Braking (iEB™) Speed limiter Power Steering Tri-Mode Dynamic Power Steering (DPS) SUSPENSIONS Front Suspension Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel Front Shocks Twin tube Rear Suspension Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel Rear Shocks Twin tube TIRES / WHEELS ITP† Terracross 26 x 8/10 x 14 in. Wheels 14 in. cast-aluminum BRAKES Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Drive Train	Selectable 4WD / 6WD / Lock 4WD with Visco-4Lok front differential
SUSPENSIONS Front Suspension Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel Front Shocks Twin tube Rear Suspension Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel Rear Shocks Twin tube TIRES / WHEELS ITP† Terracross 26 x 8/10 x 14 in. Wheels 14 in. cast-aluminum BRAKES Front Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Driving assistance	Intelligent Engine Braking (iEB™)
Front Suspension Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel Front Shocks Twin tube Rear Suspension Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel Rear Shocks Twin tube TIRES / WHEELS Front & Rear Tires Front & Rear Tires ITP† Terracross 26 x 8/10 x 14 in. Wheels 14 in. cast-aluminum BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Power Steering	Tri-Mode Dynamic Power Steering (DPS)
9.2 in. (23.3 cm) travel Front Shocks Twin tube Rear Suspension Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel Rear Shocks TIRES / WHEELS Front & Rear Tires ITP† Terracross 26 x 8/10 x 14 in. Wheels 14 in. cast-aluminum BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	SUSPENSIONS	
Rear Suspension Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25,1 cm) travel Rear Shocks Twin tube TIRES / WHEELS ITP† Terracross 26 x 8/10 x 14 in. Wheels 14 in. cast-aluminum BRAKES Eront Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Front Suspension	
with quick-release sway bar 9.9 in. (25,1 cm) travel Rear Shocks TIRES / WHEELS Front & Rear Tires ITP† Terracross 26 x 8/10 x 14 in. Wheels 14 in. cast-aluminum BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Front Shocks	Twin tube
TIRES / WHEELS Front & Rear Tires ITP† Terracross 26 x 8/10 x 14 in. Wheels 14 in. cast-aluminum BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Rear Suspension	with quick-release sway bar
Front & Rear Tires ITP† Terracross 26 x 8/10 x 14 in. Wheels 14 in. cast-aluminum BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Rear Shocks	Twin tube
Wheels 14 in. cast-aluminum BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	TIRES / WHEELS	
BRAKES Front Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Front & Rear Tires	ITP† Terracross 26 x 8/10 x 14 in.
Dual 214 mm disc brakes with hydraulic twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	Wheels	14 in. cast-aluminum
twin-piston calipers Rear Dual 214 mm disc brakes with hydraulic	BRAKES	
	Front	
	Rear	

DIMENSIONS / CAPACITIES	
Estimated Dry Weight *	1,270 lb (576 kg)
L x W x H (includes mirrors)	117 x 48 x 58.8 in. (297 x 122 x 149.4 cm)
Wheelbase	81.9 in. (208 cm)
Ground Clearance	11 in. (27.9 cm)
Seat Height	34.5 in. (87.7 cm)
Rack Capacity	Front: 45 kg / Rear: 318 kg
Storage Capacity	Dual-level cargo box with sidewalls and tailgate Rear: 18,5 gal (70 L)
Towing Capacity	2,000 lb (907 kg) trailer with brakes 1,486 lb (674 kg) trailer without brakes
Fuel Capacity	5.4 gal (20.5 L)
FEATURES	
Gauge	4.5 in. digital display

Instrumentation	DC outlet, 15-A connector
Ingnition	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	LED headlights
Winch	3,500-lb (1,588 kg) winch
Seat	Reinforced seat skin
Handlebar	Standard with heated grips & throttle
Protection	Heavy-duty front bumper

WARRANTY & EXTENDED SERVICE

Factory warranty	2-year BRP limited warranty









©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, [®] and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.